

COMPRESSOR DEFINITION

Designation	NE U4130Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	267IA50

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low-Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-35°C to 0°C	(-31°F to 32°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating (gauge)	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak (gauge)	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	12.11	[cm ³] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10	[kg] (22.05 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-0027	
3 Start capacitor	43-53(330)	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	T0156/G6	
6 Start winding resistance		[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance		[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	13.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1180	297	346	263	1.83	6.70	4.48	1.13	1.31

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	714	180	209	173	1.60	4.04	4.05	1.02	1.19
-30 (-22)	969	244	284	197	1.65	5.50	4.82	1.22	1.41
-25 (-13)	1222	308	358	225	1.70	6.94	5.44	1.37	1.59
-20 (- 4)	1504	379	441	256	1.78	8.56	5.97	1.50	1.75
-15 (+ 5)	1847	465	541	290	1.88	10.53	6.48	1.63	1.90
-10 (+14)	2280	574	668	328	2.02	13.05	7.03	1.77	2.06
-5 (+23)	2834	714	830	369	2.20	16.31	7.69	1.94	2.25
0 (+32)	3541	892	1038	413	2.42	20.48	8.52	2.15	2.50

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	623	157	182	180	1.63	3.52	3.54	0.89	1.04
-30 (-22)	924	233	271	207	1.68	5.25	4.37	1.10	1.28
-25 (-13)	1220	307	357	238	1.74	6.93	5.04	1.27	1.48
-20 (- 4)	1538	388	451	273	1.82	8.76	5.60	1.41	1.64
-15 (+ 5)	1912	482	560	312	1.93	10.91	6.14	1.55	1.80
-10 (+14)	2371	597	695	354	2.07	13.58	6.70	1.69	1.96
-5 (+23)	2946	742	863	400	2.25	16.95	7.36	1.85	2.16
0 (+32)	3667	924	1075	450	2.47	21.20	8.17	2.06	2.40

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	555	140	163	178	1.60	3.14	3.19	0.80	0.94
-30 (-22)	859	217	252	211	1.68	4.88	3.97	1.00	1.16
-25 (-13)	1151	290	337	247	1.77	6.54	4.57	1.15	1.34
-20 (- 4)	1462	368	428	287	1.88	8.32	5.06	1.27	1.48
-15 (+ 5)	1822	459	534	332	2.02	10.40	5.50	1.39	1.61
-10 (+14)	2261	570	663	380	2.19	12.95	5.96	1.50	1.75
-5 (+23)	2812	709	824	432	2.39	16.18	6.50	1.64	1.91
0 (+32)	3503	883	1027	488	2.65	20.25	7.19	1.81	2.11

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		